

POS Printer (Entry Series) CT-D150/151

USB Interface and more High Dulability Max 300 mm/sec Print Speed Auto Cutter, Buzzer as a Standard



New "Entry" Model More Features for Reliable Printing High Speed Printing with Stylish & Compact

CITIZEN SYSTEMS JAPAN CO., LTD.

CT-D150/151 POS Printer (Entry Series)

Model Name	CT-D150	CT-D151
Printing Method	Line Thermal	
Dot Configuration	576 dot/line	
Dot Density	8 dots/mm (203dpi)	
Printing Speed	Max. 250mm/sec	Max. 300mm/sec
Interface	Dual Fixed Type	Exchangeable Type
	USB2.0 + RS232C	USB2.0 + (RS232C)
	or	(Ethernet)
	USB2.0 + Ethernet	(WiFi)
	E	(Bluetooth)
Font Size	Font A: 12×24 dot (48 digits) (Kanji A: 24×24 dot)	
	Font B: 9×24 dot (64 digits)	
ANIK Ohamaatama	Font C: 8×16 dot (72 digits) (Kanji C: 16×16 dot) 96 Characters	
ANK Characters	128 Characters × 17 Countries	
Code Page International Character		
International Onaracter	12 Characters × 17 Countries Traditional Chinese (CP950 13593 Characters)	
	Simplified Chinese (GB1803-2000 28522 Characters)	
		haracters, non Kanji 989)
Barcode Type	UPC-A, UPC-E, JAN/EAN-8, JAN/EAN-13, ITF,	
	CODE39, CODE93, CODE128, CODABAR (NW-7),	
	PDF417, QR COI	DE, GS1 DataBar
Emulation	ESC/POS	
Paper Width	3inch: 79.5mm ± 0.5mm 2inch: 57.5mm ± 0.5mm	
Paper Roll Diameter	Less than φ 83mm	
Paper Thickness	53~85µm	
Life of Mechanism	20,000,000 lines	
MCBF	60,000,000 lines	
Life of Thermal Head	150km, 150 Million Pulses	200km, 200 Million Pulse
Life of Auto Cutter	2,000,000 Cut (Using 3 inch paper)	
Dimension (W×D×H)	125mm × 165mm × 108 mm	
Weight Spill Proof	Approx. 1.3kg IPX1	
Spill Proof Buzzer	Built-in	
Power	AC100V/240V, 50Hz/60Hz	
Operating Environment	5°C to 45°C (10%RH to 90%RH)	
Storaging Environment	-20°C to 60°C (10%RH to 90%RH)	
External Views and Dimension		
	20 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	
	108	1997
	125	165 (Un

•CITIZEN is a registered trademark of Citizen Watch Co., Ltd. •ENERGY STAR is a registered trademark of the United States Environmental Protection Agency in the United States and other countries. •Bluetooth[®] is a registered trademark of Bluetooth SIG, Inc. USA. •ESC/POS is a registered trademark of Seiko Epson Corporation. •QR Code[®] is a registered trademark of DENSO WAVE INCORPORATED. •The names of other companies and products are trademarks or registered trademarks of their respective companies. •Product image for illustration purposes only. Actual product may vary. •All specifications are subject to change without prior notice.

CITIZEN

CITIZEN SYSTEMS JAPAN CO., LTD.

6-1-12, Tanashi-cho, Nishi-Tokyo-shi, Tokyo 188-8511, Japan Web site: http://www.citizen-systems.co.jp/english/ Contact us: https://form.citizen.co.jp/csj/english/contact/printer-etc/form.php

Aristo Soft

Line Sale : @aristo

Tel. 02-496-0181 ถึง 4



Facebook : aristosoftware