

NEW

AS-8060



**High C/P value 1D CCD scanner
fulfill customers' demands**

Application



Jewelry Tag



Manufacturing



Transportation & Logistics



Healthcare

Feature-rich to make daily work simple and easy




2500 pixels CCD image sensor



Scan Speed >= 270 times/sec



Max. reading resolution:
3mil (0.0762mm)



Depth of Field: 15~330mm
(EAN, 13mil/0.33mm, PCS 90%)



Drop resistance:
1.5 meters onto the concrete



Auto-sensing (presentation)
mode available

Models		AS-8060
Symbologies	UPC-A, UPC-E, EAN-13, EAN-8, Codabar, Code 39 Full ASCII, China Post, Plessey, MSI, Code 93, Code 128, Industrial 2 of 5, Interleave 2 of 5, Matrix 2 of 5, Code 11, ISBN, ISSN, Code32(Italian pharmcode), Code39 extended, GS1-128 and ITF-14, SISAS, GS1 Ominidirectional, GS1 Limited, Aviation25, RSS14.	
Depth of field	25~100mm (Code39 , 4mil, PCS90%) 15~330mm (EAN, 13mil, PCS90%)	
Characteristics		
Dimensions	102mm x 71mm x 177mm	
Weight	190g	
Power	DC5V±1%	
Trigger switch	> 1,000,000 cycles	
Light source	RED LED 620nm~630nm	
Image sensor	2500 point pixel CCD image sensors	
Interface	USB-HID, USB-Virtual COM	
Indication	LED, Beeper	
Performance		
Resolution	3mil (0.0762mm)	
Print Contrast	Min. 20%	
Scan Rate	> =270 time/s	
Scan Angle	Yaw±55°, Rotation±30°, Pitch±65°	
Environment		
Light strength	70,000 Lux	
Temperature	Operating	-20°C to 50°C
	Storage	-40°C to 70°C
Humidity	5% to 95%(Non-condensing)	
Drop	Withstands multiple times 1.5meters drops to concrete	
Sealing	IP42	
Regulatory		
Regulatory Approvals	CE, FCC, BSMI	

*Argox reserves the right to enhance and modify the specification without prior notice. Please check Argox sales representative for most updated specifications.

Aristo Soft

Tel. **02-496-0181** ฝั่ง 4

Line Sale : **@aristo**

Facebook : **aristosoftware**

