

Xprinter®

Direct Thermal Barcode Printer



XP-420B

- 6 inches high speed printing
- 203 dpi resolution models
- 8MB SDRAM, 8 MB Flash
- High quality double-walled clamshell design
- Printhead temperature intelligent control system make sure printer output stably



XP-420B

Direct Thermal Printer



MODEL	XP-420B
Printing Method	Direct Thermal
Resolution	8 dots/mm(203 DPI)
Interface	USB2.0 (Standard) / Lan(Optional) / Bluetooth(Optional) / WIFI(Optional) /
Optional accessories	TF card slot, RTC clock, Peel off module, Cutter module
Max Print Speed	152 mm (6") / s
Max Print Width	108mm (4.25")
Max Print Length	1778mm
Media Type	Continuous, gap, black mark, fan-fold and punched hole
Media Width	20 mm ~ 115 mm
Media Thickness	0.06 mm ~ 0.25 mm
Media Length	10 mm ~1778 mm
Paper roll diameter	25.4 ~ 76.2 mm (1" ~ 3")
Paper thickness	0.06 mm ~ 0.25 mm
Label Roll Capacity	127 mm (5") external diameter
Memory	8MB Flash Memory
	8MB SDRAM
	Micro SD card reader for Flash memory expansion, up to 4GB
Sensor	Gap sensor
	Printer Head opened sensor
	Black mark sensor
Processor	32-bit RISC CPU
Power Supply	Input: AC 100-240V; Output: DC 24V/2.5A
Barcode	1D barcode: Code 39, Code 93, Code 128UCC, Code 128, subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8,EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code11
	2D barcode: PDF-417, Maxicode, DataMatrix, QR code, Aztec
Emulation	TSPL \ EPL \ ZPL \ DPL
Dimension	215 mm x 178 mm x 155 mm
Weight	1.31 kg
Safety Standard	FCC, CE, CB, CCC
Environment	Operation condition: -10 ~ 50 °C (14 ~ 122 °F) ,10 ~ 90% non-condensing
	Storage condition : -40 ~ 60 °C (-40 ~ 140 °F), 10 ~ 90% non-condensing

Aristo Soft

Tel. 02-496-0181 ฝั่ง 4

Line Sale : @aristo

Facebook : aristosoftware

